

IRIDIUM[™] HANDHELD TRACKER: SHOUT nano



- Low-cost tracker and messaging device
- Programmed for either DoD or commercial Iridium gateway
- ✓ Ultra-low power consumption
- Automatic location reports (>1200 reports)
- ✓ Guarded 911 alert switch
- ✓ Waypoint soft key
- Check-in soft key
- Free-text, canned messages or combined free-text and canned messages
- Data logging (waypoints and tracking reports)
- 256-bit AES encryption
- ✓ Real-time, pole-to-pole coverage
- ✓ Weighs ~6.5 ounces
- ✓ Volume of 4.0" x 2.2" x 0.8
- Internal rechargeable battery using AC adapter, computer
 USB port or solar charger
- ✓ Integrated motion sensor
- ✓ USB interface
- ✓ 50-channel GPS receiver with -160 dBm sensitivity

IRIDIUM HANDHELD TRACKER POWERED by the IRIDIUM NETWORK

HANDHELD TRACKER/MESSAGING DEVICE: SHOUT nano

The SHOUT nano is a handheld, global, two-way satellite messaging and personal tracking device. It utilizes Iridium's short burst data (SBD) service to provide location information determined by a GPS receiver, two-way inbound and outbound status, text messaging, and emergency/alert notifications. The nano measures $4.0^{"} \times 2.2^{"} \times 0.8^{"}$ and weighs ~6.5 ounces.

The nano is designed with ultra-low power consumption electronics drawing less than 35μ A during sleep. With an internal 1.95 A-Hr rechargeable Li-Ion battery, it can send a position report every hour for up to two months (about 1,200 reports). The nano is equipped with a high resolution color LCD and onscreen keyboards supporting transmission of free-text, canned messages and a combination of free-text and canned messages. The menu options are displayed as icons for quick access. The device can periodically wake up from sleep to send its position report to a command center. A 911 button is used for immediate emergency/alert notifications. Data are packaged in either standard or 256-bit AES encrypted format. Data can also be sent in encrypted PECOS formats to include Brevity codes.

The nano offers a variety of services including:

- Normal Tracking programmed to automatically wake up and send a position report at a set interval ranging from continuous to once every seven days.
- Emergency Alert sends alerts to a designated monitoring center using a 911 button. The monitoring center and the user can then communicate to define further specifics of the emergency.
- Free-Text Messaging sends free-text via three different sets of onscreen keyboards.
- Canned Text Messaging sends canned (pre-defined) messages in short codes to save bandwidth instead of the entire message body.
- Waypoint Tracking sends and/or saves waypoints (interested landmarks) for later retrieval.
- Check-In allows a quick check-in message to be sent using a single soft key.



IRIDIUM[™] HANDHELD TRACKER: SHOUT nano



- ✓ Pocket-size, self-contained satellite tracker
- ✓ Ultra-low power consumption
- \checkmark AES 256-bit encryption both transmit/receive
- ✓ Two-way communications
- ✓ Real-time reporting
- ✓ Truly global coverage

Specifications

Mechanical	
Dimensions:	4.0" L x 2.2" W x 0.8" D
Weight:	~6.5 Oz
I/O Interface:	USB
Cooling:	Convection
Enclosure:	Hard-Anodized Aluminum
Electrical	
Input Voltage Range:	2.7VDC to 5.5VDC
Input Nominal Voltage:	4.0VDC
Power consumption during standby:	less than $35\mu A \ @ 5.0VDC$
Power Input Type:	External DC power or internal battery
Iridium RF Board	
Operating Frequency:	1616 to 1626.5 MHz
Link Margin Downlink:	13 dB average
Link Margin Uplink:	7 dB average
Average Power Transmission:	1.0 W
GPS Receiver	
Receiver Type:	1575.42 MHz (L1), 50-channel, C/A code
Accuracy:	2.5 m CEP
Update Rate:	4 Hz
Start-up Times:	< 1 sec hot start, 29 sec warm start and 29 sec cold start
Sensitivity:	-160 dBm
Environmental	
Operating Temperature:	-40°F to +185°F (-40°C to +85°C)
Operating Humidity:	< 75% RH



www.nalresearch.com 9300 West Courthouse Road, Manassas, Virginia 20110 USA

IRIDIUM[™] HANDHELD TRACKER: SHOUT nano

1

2



- Power/Enter: 1. Turns device ON/OFF when hold down for two seconds or 2. Used to select highlighted item on the menu.
- Arrow Up/Down/Right: Used to navigate the cursor.
- Arrow Left: 1. Used to navigate the cursor or
 - 2. Used to go back to the previous menu.
- 3) Check-In Soft Key: Used to access the Check-In feature.
- 4) Way Point Soft Key: Used to access the Way Point features.
- 5 USB Port: Used to charge the battery, update firmware or setup operating parameters using a computer.
- 6) Emergency: Used to send an emergency alert/notification.
- 7) Guard: Protects emergency button from being accidentally activated.
- 8) LED: Displays tracking and emergency statuses.
- 9) Antenna: GPS antenna.
- 10) Antenna: Iridium antenna.

